

MARATHON ELECTRIC GENERATORS TYPICAL SUBMITTAL DATA

Section 3660

Page 1

MODEL : 282PSL1514
BASE MODEL : 282PSL1514

Winding WC- 1514

10/31/2001

Kilowatt ratings at kW (kVA)	1800 RPM		60 Hertz			4 LEADS		Dedicated single phase Dripproof or Open Enclosure		
	Class B		Class F					Class H		
	80° C Ø Continuous	90° C Ø Lloyds	95° C Ø ABS	105° C British Standard	105° C Continuous	130° C Ø Standby	125° C British Standard	125° C Continuous	150° C Ø Standby	
240-1	10.5 (10.5)	11 (11)	11 (11)	12 (12)	12 (12)	13 (13)	13 (13)	13 (13)	13.5 (13.5)	
240-8	7 (8.8)	7.4 (9.3)	7.5 (9.4)	7.7 (9.6)	7.7 (9.6)	8.4 (10.5)	8.4 (10.5)	8.5 (10.6)	9 (11.3)	
220-1	10 (10)	10.5 (10.5)	10.5 (10.5)	11 (11)	11 (11)	12 (12)	12 (12)	12 (12)	12.5 (12.5)	
220-8	7 (8.8)	7.4 (9.3)	7.4 (9.3)	7.7 (9.6)	7.7 (9.6)	8.5 (10.6)	8.5 (10.6)	8.5 (10.6)	9 (11.3)	

① Rise by resistance method, Mil-Std-705, Method 680.1b.

British Standard Rating per BS 5000

Submittal Data: 240 Volts*, 7.68 kW, 9.6 kVA, 0.8 P.F., 1800 RPM, 60 Hz, 1 Phase

Mil-Std-705B			Mil-Std-705B		
Method	Description	Value	Method	Description	Value
301.1b	Insulation Resistance	>1.5 Meg	505.3b	Overspeed	2250 RPM
302.1a	High Potential Test		601.4a	L-L Harmonic Maximum - Total (Distortion Factor)	8.0%
	Main Stator	1500 Volts	601.4a	L-L Harmonic Maximum - Single	7.0%
	Main Rotor	1500 Volts	601.1c	Deviation Factor	8.0%
	Exciter Stator	1500 Volts	--	Type	MAGNAPLUS
	Exciter Rotor	1500 Volts	--	Insulation	Class H
401.1a	Stator resistance - Line to Line		--	Coupling - Single Bearing	Flexible
	Dedicated connection	0.436 Ohms	--	Amortisseur Windings	Full
	Rotor Resistance	0.45 Ohms	--	Exciter	Rotating
	Exciter Stator	23 Ohms	--	Voltage Regulator	SE350
	Exciter Rotor	0.12 Ohms	--	Voltage Regulation	1.00%
410.1a	No Load Exciter Field Amps at 240 Volts Line to Line	0.4 A DC	--	Cooling Air Volume	250 CFM

