

MARATHON ELECTRIC GENERATORS TYPICAL SUBMITTAL DATA

Section

Page

MODEL : 572RSL4025
BASE MODEL : 572RSL4025

Winding H-SG 570078S

11/01/2001

Kilowatt ratings at kW (kVA)	1800 RPM		60 Hertz			12 LEADS		Single phase connection Dripproof or Open Enclosure		
	Class B		Class F					Class H		
	80° C \emptyset Continuous	90° C \emptyset Lloyds	95° C \emptyset ABS	105° C British Standard	105° C Continuous	130° C \emptyset Standby	125° C British Standard	125° C Continuous	150° C \emptyset Standby	
480/240-1	209 (209)	209 (209)	209 (209)	248 (248)	248 (248)	261 (261)	261 (261)	261 (261)	278 (278)	
480/240-8	167 (209)	167 (209)	167 (209)	198 (248)	198 (248)	209 (261)	209 (261)	209 (261)	222 (278)	
440/220-1	0 (0)	0 (0)	0 (0)	0 (0)	0 (0)	0 (0)	0 (0)	0 (0)	0 (0)	
440/220-8	0 (0)	0 (0)	0 (0)	0 (0)	0 (0)	0 (0)	0 (0)	0 (0)	0 (0)	

① Rise by resistance method, Mil-Std-705, Method 680.1b.

British Standard Rating per BS 5000

Submittal Data: 480 Volts*, 198.4 kW, 248 kVA, 0.8 P.F., 1800 RPM, 60 Hz, 1 Phase					
Mil-Std-705B			Mil-Std-705B		
Method	Description	Value	Method	Description	Value
301.1b	Insulation Resistance	>1.5 Meg	505.3b	Overspeed	2250 RPM
302.1a	High Potential Test		601.4a	L-L Harmonic Maximum - Total (Distortion Factor)	5.0%
	Main Stator	2000 Volts	601.4a	L-L Harmonic Maximum - Single	5.0%
	Main Rotor	1500 Volts	601.1c	Deviation Factor	6.0%
	Exciter Stator	1500 Volts	--	Type	MAGNAMAXDVR
	Exciter Rotor	1500 Volts	--	Insulation	Class H
401.1a	Stator resistance - Line to Line		--	Coupling - Single Bearing	Flexible
	Low-Zigzag = 0.005 Ohms, Hi-Zigzag = 0.02 Ohms		--	Amortisseur Windings	Full
	Rotor Resistance	0.376 Ohms	--	Exciter	Rotating
	Exciter Stator	23 Ohms	--	Voltage Regulator	DVR2000
	Exciter Rotor	0.045 Ohms	--	Voltage Regulation	0.25%
410.1a	No Load Exciter Field Amps at 240/480 Volts Line to Line	0.7 A DC	--	Cooling Air Volume	1550 CFM

