

MARATHON ELECTRIC GENERATORS TYPICAL SUBMITTAL DATA

Section 3650

Page 20

MODEL : 431PSL6208
BASE MODEL : 431PSL6208

Winding WC- 1903S

11/01/2001

Kilowatt ratings at kW (kVA)	1800 RPM		60 Hertz			12 LEADS		Single phase connection Dripproof or Open Enclosure		
	Class B		Class F					Class H		
	80° C Ø Continuous	90° C Ø Lloyds	95° C Ø ABS	105° C British Standard	105° C Continuous	130° C Ø Standby	125° C British Standard	125° C Continuous	150° C Ø Standby	
480/240-1	131 (131)	135 (135)	135 (135)	150 (150)	150 (150)	166 (166)	154 (154)	165 (165)	175 (175)	
480/240-8	105 (131)	108 (135)	108 (135)	120 (150)	120 (150)	132 (165)	123 (154)	130 (163)	136 (170)	
440/220-1	0 (0)	0 (0)	0 (0)	0 (0)	0 (0)	0 (0)	0 (0)	0 (0)	0 (0)	
440/220-8	0 (0)	0 (0)	0 (0)	0 (0)	0 (0)	0 (0)	0 (0)	0 (0)	0 (0)	

① Rise by resistance method, Mil-Std-705, Method 680.1b.

British Standard Rating per BS 5000

Submittal Data: 480 Volts*, 140 kW, 175 kVA, 0.8 P.F., 1800 RPM, 60 Hz, 1 Phase					
Mil-Std-705B			Mil-Std-705B		
Method	Description	Value	Method	Description	Value
301.1b	Insulation Resistance	>1.5 Meg	505.3b	Overspeed	2250 RPM
302.1a	High Potential Test		601.4a	L-L Harmonic Maximum - Total (Distortion Factor)	5.0%
	Main Stator	2000 Volts	601.4a	L-L Harmonic Maximum - Single	5.0%
	Main Rotor	1500 Volts	601.1c	Deviation Factor	6.0%
	Exciter Stator	1500 Volts	--	Type	MAGNAPLUS
	Exciter Rotor	1500 Volts	--	Insulation	Class H
401.1a	Stator resistance - Line to Line		--	Coupling - Single Bearing	Flexible
	Low-Zigzag = 0.0131 Ohms, Hi-Zigzag =	0.0524 Ohms	--	Amortisseur Windings	Full
	Rotor Resistance	0.709 Ohms	--	Exciter	Rotating
	Exciter Stator	18.5 Ohms	--	Voltage Regulator	SE350
	Exciter Rotor	0.116 Ohms	--	Voltage Regulation	1.00%
410.1a	No Load Exciter Field Amps at 240/480 Volts Line to Line	0.6 A DC	--	Cooling Air Volume	1100 CFM

