

MARATHON ELECTRIC GENERATORS TYPICAL SUBMITTAL DATA

Section 0

Page 0

MODEL : 431PSL6224
BASE MODEL : 431PSL6224

Winding H-SG 430628

11/01/2001

Kilowatt ratings at kW (kVA)	1800 RPM		60 Hertz			4 LEADS		Dedicated single phase Dripproof or Open Enclosure		
	Class B		Class F					Class H		
	80° C Ø Continuous	90° C Ø Lloyds	95° C Ø ABS	105° C British Standard	105° C Continuous	130° C Ø Standby	125° C British Standard	125° C Continuous	150° C Ø Standby	
240-1	130 (130)	135 (135)	135 (135)	145 (145)	145 (145)	155 (155)	155 (155)	155 (155)	165 (165)	
240-8	80 (100)	85 (106)	85 (106)	90 (113)	90 (113)	100 (125)	100 (125)	100 (125)	110 (138)	
220-1	120 (120)	125 (125)	125 (125)	135 (135)	135 (135)	145 (145)	145 (145)	145 (145)	155 (155)	
220-8	80 (100)	85 (106)	85 (106)	95 (119)	95 (119)	100 (125)	100 (125)	100 (125)	110 (138)	

① Rise by resistance method, Mil-Std-705, Method 680.1b.

British Standard Rating per BS 5000

Submittal Data: 240 Volts*, 132 kW, 165 kVA, 0.8 P.F., 1800 RPM, 60 Hz, 1 Phase					
Mil-Std-705B			Mil-Std-705B		
Method	Description	Value	Method	Description	Value
301.1b	Insulation Resistance	>1.5 Meg	505.3b	Overspeed	2250 RPM
302.1a	High Potential Test		601.4a	L-L Harmonic Maximum - Total (Distortion Factor)	5.0%
	Main Stator	1500 Volts	601.4a	L-L Harmonic Maximum - Single	5.0%
	Main Rotor	1500 Volts	601.1c	Deviation Factor	6.0%
	Exciter Stator	1500 Volts	--	Type	MAGNAPLUS
	Exciter Rotor	1500 Volts	--	Insulation	Class H
401.1a	Stator resistance - Line to Line		--	Coupling - Single Bearing	Flexible
	Dedicated connection	0.0129 Ohms	--	Amortisseur Windings	Full
	Rotor Resistance	0.615 Ohms	--	Exciter	Rotating
	Exciter Stator	18 Ohms	--	Voltage Regulator	SE350
	Exciter Rotor	0.105 Ohms	--	Voltage Regulation	1.00%
410.1a	No Load Exciter Field Amps at 240 Volts Line to Line	0.6 A DC	--	Cooling Air Volume	1100 CFM

